

Nastri e rotoli abrasivi in tela per sbavatura e finitura
Abrasive cloth belts and rolls for grinding and finishing

Tipo / Type	Grane / Grits						
	24	36	40	50	60	80	100+
XA517	•	•	•	•	•	•	•
PA631	•	•	•	•	•	•	•
JA512	•	•	•	•	•	•	•
KZ563	•	•	•	•	•	•	•
PZ633/628	•	•	•	•	•	•	•
PS992	•	•	•	•	•	•	•



Giunzioni (solo per nastri abrasivi)
N = Normale, saldatura sovrapposta
TT = Testa-testa con pellicola speciale

Joints (for abrasive belts only)
N = Standard, superposed joint
TT = Head to head with special film

Tipo / Type	Grane / Grits			
	A - Coarse	A - Medium	A - Very Fine	S/Ultra Fine
Surf. Cond. Low Stretch	•	•	•	•

Tipo Hi-Flex disponibile / Hi-Flex Type available

Giunzioni (solo per nastri abrasivi)
TT = Testa-testa con pellicola speciale

Joints (for abrasive belts only)
TT = Head to head with special film

Rotoli - Rolls

Misura/Size mm x m.	Grane / Grits							
	40	50	60	80	100	120	150-400	
RTE 115x50	•	•	•	•	•	•	•	4

Fogli - Sheets

Misura/Size mm x m.	Grane / Grits							
	40	50	60	80	100	120	150-400	
FTE 230x280	•	•	•	•	•	•	•	100 X 3

Caratteristiche tecniche e applicazioni / Technical features and application

Tipo / Type	Supporto / Backing	Legante Bond	Abrasivo / Abrasive	Applicazioni / Application
KA 164	Cotone / Cotton Peso J-Flex / J-Flex weight	R/R	Al.Ox. Grane / Grits 24-400	Uso a secco / Dry use Uso a mano / Handy use Per metallo/legno For metal/wood
XA517	Poliestere / Cotone Polyester / Cotton Peso X / X weight	R/R	Al.Ox. Grane / Grits 24-400	Uso a secco / Dry use Per ferro/acciai/inox/legno duro For iron/steels/inox/hard wood
PA631	Poliestere / Polyester Peso Y / Y weight	R/R	Al.Ox. Speciale Special Al.Ox. Grane / Grits 24-600	Uso a secco e umido / Dry and wet use Per ferro/acciai/inox/ leghe Ni-Co/fusioni di Al-Zn For iron/steels/inox/Ni-Co alloys/ Al-Zn meltings
JA512	Poliestere / Cotone Polyester / Cotton Peso J-Flex J-Flex weight	R/R	Al.Ox. Speciale Special Al.Ox. Grane / Grits 60-600	Uso a secco / Dry use Per inox/acciai al carbonio/leghe di Al/ legno duro For inox/carbon-steels/Al. alloys/hard wood
KZ563	Cotone / Cotton Peso X / X weight	R/R	Zirconio Zirconia Ox. Grane / Grits 24-120	Uso a secco / Dry use Per ferro/acciai/inox For iron/steels/inox
PZ633 (PZ628)	Poliestere / Polyester Peso Y / Y weight PZ 628 peso YY / YY weight	R/R	Zirconio speciale Special Zirconia Ox. Grane / Grits 24-120	Uso a secco e umido / Dry and wet use Per acciai/inox/leghe For steels/inox/alloys
PS992	Poliestere / Polyester Peso Y / Y weight	R/R	Al.Ox. Ceramicato Ceramic Al.Ox. Grane / Grits 24-120	Uso a secco / Dry use Per acciai/inox/leghe for steels/inox/alloys
Surface Conditioning	Tessuto-non-tessuto Tipo Low-stretch Non woven tissue Low stretch type			Finitura superficiale / Surfaces finishing Per acciai/inox/leghe For steels/inox/alloys