

SPRAY ABRA+ : Trattamento anti-intasamento per abrasivi

SPRAY ABRA+ : Anti-clogging treatment for abrasives

AEROSOL			
ABRA+ (400 ml)	•		4

Aerosol che prolunga la durata dell'utensile abrasivo; agisce limitando al minimo gli effetti di intasamento da sovrametallo e deposito di materiale levigato, riducendo il tempo di molatura, diminuendo l'effetto di surriscaldamento. Specifico per lavorazioni su alluminio e leghe, acciai inox, etc. Adatto per nastri abrasivi, dischi lamellari, fibrodischi, dischi velcrati, etc. Non contaminante per le superfici.

Aerosol for a longer lifetime of the abrasive tool ; act minimizing clogging effects due to storage of removed material ,reducing overheating: Specific for aluminium and alloys, stainless steel, etc. Suitable for abrasive belts, flap discs, fibrediscs, velcrum discs, etc. Not polluting for surfaces.



Dischi abrasivi semirigidi

Semi-rigid sanding discs

Per smerigliatura e finitura con macchine portatili a 80 m/s.

For grinding and finishing on 80 m/s portable machines.

Tipo/Type	SRP*		SRS		
	Ferro-Acciai Iron-Steels	Marmo Vetroresina Marble Fibreglass	Ferro-Acciai Iron-Steels	Marmo Vetroresina Marble Fibreglass	
Ø mm x Ø	A	C	A	C	
115x22	•	•	•	•	50
125x22	•	•	•	•	50
180x22	•	•	•	•	50

SRP*

Disco semirigido pesante

Strato abrasivo resinoide spesso su fibra vulcanizzata

Heavy semi-rigid disc

Thick abrasive resinoid layer on vulcanised fibre backing

SRS

Disco semirigido speciale

Strato abrasivo resinoide spesso su fibra di vetro

Special semi-rigid disc

Thick abrasive resinoid layer on fibreglass backing

*Utilizzare con platorello / Use with suitable backing pad.



Dischi Surface Conditioning

Surface Conditioning Discs

Grane / Grits Colore / Colour	Very Fine Azzurro / Blue	Medium Rosso / Red	Coarse Marrone / Brown	Max r.p.m.	
DVC Ø 115 mm	•	•	•	13.300	40
DVC Ø 125 mm	•	•	•	12.200	40
DVC Ø 180 mm	•	•	•	8.600	20

Platorelli speciali ad attacco rapido per DVC con filetto M14

Special quick - clamping back up pads for DVC with M14 threading

Articolo / Item					
PLAØ 115 mm	DVC Ø115		•		1
PLAØ 125 mm	DVC Ø125		•		1
PLAØ 180 mm	DVC Ø180		•		1

